













M3W EN-Series (Meet EU Standards)



-  Ethernet for stable connection
-  WIFI for convenient home use
-  OCPP communication with CMS
-  Tethered and integrated socket meet different demands
-  Special one-piece metal backcover
-  4.3-inch highlight display
-  4G optional for any location
-  Rs485 interface enable Dynamic Load Balancing and Solar Charging
-  Smart app with full function
-  Wall-mount or floor stand installation
-  Anti-scraping tempered glass front cover
-  Type A 30ma + 6ma DC leakage protection CE, ROHS, REACH, LVD, RED approved



Item		M3W132EN	M3W316EN	M3W332EN
Maximum Power		7kW/32A -230VAC	11kW/16A -400VAC	22kW/32A -400VAC
Basic info	Tethered/Socket	Optional		
	Connector	Type 2		
	Dimension(H*W*D)mm	410*260*164		
	Material	Tempered glass front+metal plate back		
	Colour	BLACK front + white back or OEM Color		
	Indicator	4 indicators		
	Display	4.3-inch		
Features	Ethernet(RJ45)	Yes		
	RFID	Yes		
	WIFI	2.4GHz		
	4G	Optional		
	RS485	Optional		
	OCPP1.6J	Optional		
	App	Optional		
	Dynamic Load Balancing	Optional		
	Solar Charging	Optional		
Safety	Ingress Protection	IP54, IK08		
	Residual current protection	Type A 30mA+6mA DC		
	Over load protection	Yes		
	Over/Under voltage protection	Yes		
	Short circuit protection	Yes		
	Earh Leakage Protection	Yes		
	Ground Protection	Yes		
	Surge protection	Yes		
	Over temperature	Yes		
	Certification	CE, RoHS, Reach, LVD, RED		
	Certification Standard	EN IEC 61851-1		
Environment	Installation	Wall/Pole mounted		
	Storge Temperature	-40~75°C		
	Work Temperature	-30~55°C		
	Work Humidity	3%~95%		
	Work Altitude	<2000m		